


Code: 115532-00



The new Disanlens ceiling fixture is the ideal solution to ensure maximum visual comfort in places like classrooms and offices that require optimal lighting distribution.



Article	604 - Disanlens
Code	115532-00

DIMENSIONS AND WEIGHT

Length (mm)	594 mm
Width (mm)	152 mm
Height (mm)	55 mm
Weight (Kg)	1.3 kg


ELECTRICAL CHARACTERISTICS AND CONTROLS

Voltage type	AC
Min Voltage (V)	220 V
Max Voltage (V)	240 V
Min Frequency (Hz)	50 Hz
Max Frequency (Hz)	60 Hz
Frequency (Hz)	50 Hz
Wiring name	CLD
Power factor	≥0.9
Insulation class	Class I
Controllability	None

604 - Disanlens

Code: 115532-00

PHOTOMETRIC DATA



Lighting source	LED
CRI	80
Luminous flux (output) (lm)	1513 lm
Power absorption (total) (W)	12 W
CCT	4000 K
Luminous efficacy (lm/W)	126 lm/W
LED flux maintenance	50000 hr, L 90, B 10




MECHANICAL CHARACTERISTICS

Impact resistance rating (IK)	IK06
IP	40



604 - Disanlens

Code: 115532-00



DOWNLOAD

MOUNTS

AssemblyInstructions 603-604 10-24.pdf

DESIGNS

BIM 604 Disanlens 03-25.zip

TechnicalDrawing 603-604.dxf



MATERIALS AND COLOURS

Housing	in pressed steel sheet, white ABS end caps.
Diffuser	in polycarbonate with an outer micro-prismatic finish to control light distribution.
Colour	White
Equipment	with cable entry grommet and spacers for ceiling/wall mounting.

EMERGENCY LIGHTING

Emergency power supply type	Not present
-----------------------------	-------------

STANDARDS AND COMPLIANCE

Photobiological safety class	RG0
Markings and tests	CE
Reference standards	EN60598-1. They have a degree of protection according to the EN60529 standard. EN60598-22-2.
Energy Label	C

GEAR

Sensors	
Upon request	Emergency versions

WARRANTY

After sales warranty	3 yr
----------------------	------

604 - Disanlens

Code: 115532-00

