## 6003 - Power track - without connector

Code: 132972-00

| IK08 IP40 |  | And |
|-----------|--|---|
|-----------|--|---|

POWER TRACK 11 POLES 6003 L=2842MM WHI



|             |  | GENERAL INFORMATION   |
|-------------|--|-----------------------|
| Article     | 6003 - Power track - without connector |                       |
| Code        | 132972-00                              |                       |
|             |  | DIMENSIONS AND WEIGHT |
| Length (mm) | 2842 mm                                |                       |
| Width (mm)  | 60 mm                                  |                       |
| Height (mm) | 40 mm                                  |                       |
| Weight (Kg) | 3.5 kg                                 |                       |



Please contact the Consulting and Design Centre for any technical information. The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The total wattage absorbed by the system will not exceed 10% of the reported value. Technical lighting data may be subject to changes and improvements due to the fast evolution of the technology. Wednesday, December 25, 2024

Code: 132972-00







Please contact the Consulting and Design Centre for any technical information. The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The total wattage absorbed by the system will not exceed 10% of the reported value. Technical lighting data may be subject to changes and improvements due to the fast evolution of the technology. Wednesday, December 25, 2024

## 6003 - Power track - without connector

Code: 132972-00





|                     | MATERIALS AND COLOURS  |  |
|---------------------|--|--|
| Housing             | Track body: galvanized rolled steel. With anti-cutting turned-up edges and complete with 1.5 mm2 cables. |  |
| Coating             | pre-painted in oven with polyester resin, UV-stabilized, phosphate pre-<br>treatment.                    |  |
| Colour              | White  |  |
|                     | STANDARDS AND COMPLIANCE   |  |
| Reference standards | EN60598-1. With degree of protection according to EN60529.   |  |
|                     | WARRANTY   |  |

## DOWNLOAD

After sales warranty

0 yr

MOUNTS

AssemblyInstructions 6001-6002-6003 mount examples.pdf

DESIGNS

TechnicalDrawing chanEL.dxf







Please contact the Consulting and Design Centre for any technical information. The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The total wattage absorbed by the system will not exceed 10% of the reported value. Technical lighting data may be subject to changes and improvements due to the fast evolution of the technology. Wednesday, December 25, 2024