3116 - Ghost LED - Diffuser with micro-satin finish





3116 Ghost LED - Diffuser with micro-satin finish



	GENERAL IN	FORMATION
Article	3116 - Ghost LED - Diffuser with micro-satin finish	
Code	322929-00	
	DIMENSIONS A	ND WEIGHT
Height (mm)	460 mm	
Diameter (Ø) (mm)	400 mm	
Weight (Kg)	3.3 kg	
	ELECTRICAL CHARACTERISTICS AND	CONTROLS
Voltage type	AC	
Min Voltage (V)	220 V	
Max Voltage (V)	240 V	
Min Frequency (Hz)	50 Hz	
Max Frequency (Hz)	60 Hz	
Frequency (Hz)	50 Hz	
Wiring name	CLD	
Power factor	≥0.95	
Insulation class	Class I	
Controllability	None	



3116 - Ghost LED - Diffuser with micro-satin finish

Code: 322929-00
7150
105
96
85
75
654
55
45

Lighting source	LED	
CRI	80	
Luminous flux (output) (lm)	4325 lm	
Power absorption (total) (W)	38 W	
ССТ	4000 K	
Luminous efficacy (lm/W)	114 lm/W	
LED flux maintenance	50000 hr, L 80, B 20	
LED flux maintenance	50000 hr, L 80, B 20	MECHANICAL CHARACTERISTICS
LED flux maintenance Impact resistance rating (IK)	50000 hr, L 80, B 20 IK08	MECHANICAL CHARACTERISTICS
		MECHANICAL CHARACTERISTICS





PHOTOMETRIC DATA

Ambient temperature - max

30 °C

3116 - Ghost LED - Diffuser with micro-satin finish

Code: 322929-00

Housing	in die-cast aluminium with cooling fins integrated in the cover.
Diffuser	in transparent polycarbonate, internally prismatic for greater light control and externally smooth, dustproof and impact-resistant, shatterproof, V2 self-extinguishing, UV stablised.
Heat sink	cooling fins integrated in the cover.
Coating	pre-treatment of metal surface, polyester powder coating to ensure resistance to corrosion and salt spray fogs, UV stabilised.
Colour	Grey9007
Equipment	- removable wiring block plate - hook for suspension mounting rubber cable grommet with diam. 1/2 gas inch (cable min. diam.9 max diam. 12)

STANDARDS AND COMPLIANCE

MATERIALS AND COLOURS

Photobiological safety class	RG0 Ethr
Markings and tests	CE
Reference standards	EN60598-1. With degree of protection according to EN60529.
Energy Label	D

3 yr

WARRANTY

DOWNLOAD

After sales warranty

MOUNTS

AssemblyInstructions ghost 03-23.pdf

Ø400

DESIGNS

TechnicalDrawing 3116.dxf



