

1727 - Cripto COB big - asymmetric

Code: 413150-73



Disano presents a lighting fixture, designed as a possible retrofit for more classic models. The excellent performance of this luminaire in terms of energy saving and luminous efficiency is accompanied by a long lifespan, with IP66-rated materials for outdoor installations. The most advanced technology and design are used to reduce consumption and address the increasing need to replace obsolete equipment and save energy.



GENERAL INFORMATION

Article	1727 - Cripto COB big - asymmetric
Code	413150-73

DIMENSIONS AND WEIGHT

Length (mm)	500 mm
Width (mm)	360 mm
Height (mm)	82 mm
Weight (Kg)	6 kg

INSTALLATION

Surface exposed to wind (mm)	L 30800 mm ² , F 126000 mm ²
------------------------------	--


ELECTRICAL CHARACTERISTICS AND CONTROLS

Voltage type	AC
Min Voltage (V)	220 V
Max Voltage (V)	240 V
Min Frequency (Hz)	50 Hz
Max Frequency (Hz)	60 Hz
Frequency (Hz)	50 Hz
Wiring name	CLD
Power factor	≥0.92
Surge protector (common) (EN 61547)	2 kV, 4 kV
Insulation class	Class II
Controllability	None

1727 - Cripto COB big - asymmetric

Code: 413150-73

PHOTOMETRIC DATA



Distribution type	Asymmetric
Lighting source	LED COB AMBER
CRI	amber
Luminous flux (output) (lm)	14266 lm
Power absorption (total) (W)	127 W
CCT	2200 K
Luminous efficacy (lm/W)	112 lm/W
Low Flicker	luminaire with very low flicker: evenly distributed light for greater visual safety.
LED flux maintenance	50000 hr, L 90, B 10


MECHANICAL CHARACTERISTICS

Impact resistance rating (IK)	IK09
IP	66
Ambient temperature - min	-30 °C
Ambient temperature - max	40 °C

1727 - Cripto COB big - asymmetric

Code: 413150-73

MATERIALS AND COLOURS



DOWNLOAD

MOUNTS

AssemblyInstructions cripto 12-23.pdf

DESIGNS

BIM 1727 09-25.zip

TechnicalDrawing 1727i.dxf



Housing	in die-cast aluminium, with cooling fins.
Optics	in high gloss faceted aluminium.
Diffuser	tempered glass, 4 mm thick, resistant to thermal shock and impact (UNI EN 12150-1:2001).
Heat sink	the heat sink is designed and made to allow the LEDs to operate at temperatures capable of ensuring excellent performance/output and long service life.
Coating	the fully automated powder-coating cycle involves a polyester-based, salt-spray corrosion-resistant and UV-stabilised paint.
Special coating (UPON REQUEST)	Upon request: protective coating recommended for marine environments within 5 km (3 miles) of the sea.
Colour	Graphite
Equipment	- with galvanised and painted bracket - EN 61547 compliant surge protection - silicone rubber gasket - external screws and bolts in stainless steel.
	Luminous flux maintenance 70%: 100.000h (L70B50) o luminous flux maintenance 90%: 50.000h (L90B10).

STANDARDS AND COMPLIANCE

Photobiological safety class	RG0 Ethr
Markings and tests	CE
Reference standards	EN60598-1. They have a degree of protection according to the EN60529 standard.
Energy Label	E

GEAR


Sensors	
Upon request	- protection of up to 10kV - AMBER LED 2200K subcode -73 - CLD-D (1-10V) wiring, subcode -12 - CLD-D-D (DALI) wiring, subcode -0041 - possibility of central light management or with external presence/light sensors.

WARRANTY

After sales warranty	5 yr
----------------------	------

1727 - Cripto COB big - asymmetric

Code: 413150-73



625 Conveyor big