

Code: 414741-39



The Rodio family comprises several versions, with asymmetric, narrow-beam and wide-beam optics, also available in wide beam and street curve versions, and Virtual Midnight option. Equipped with LEDs, these luminaires offer perfect glare-free light control. You can choose versions with lenses or with COB LEDs for better lighting performance. All models feature high light quality, colour temperatures of 3000 or 4000K and excellent colour rendering. Also available in Amber colour versions.



Article	1887 - Rodio HE - asymmetric
Code	414741-39

Length (mm)	568 mm
Width (mm)	333 mm
Height (mm)	90 mm
Weight (Kg)	8.1 kg


Surface exposed to wind (mm)	L 45500 mm ² , F 152900 mm ²
------------------------------	--

Voltage type	AC
Min Voltage (V)	220 V
Max Voltage (V)	240 V
Min Frequency (Hz)	50 Hz
Max Frequency (Hz)	60 Hz
Frequency (Hz)	50 Hz
Wiring name	CLD
Power factor	≥0.9
Surge protector (common) (EN 61547)	10 kV, 10 kV
Insulation class	Class I
Controllability	None

1887 - Rodio HE - asymmetric

Code: 414741-39

PHOTOMETRIC DATA



Distribution type	Asymmetric
Lighting source	LED
CRI	80
Luminous flux (output) (lm)	17196 lm
Power absorption (total) (W)	102 W
CCT	3000 K
Luminous efficacy (lm/W)	169 lm/W
Low Flicker	luminaire with very low flicker: evenly distributed light for greater visual safety.
Colour consistency	SDCM4
Asymmetry degrees	55 °
LED flux maintenance	100000 hr, L 90, B 10


MECHANICAL CHARACTERISTICS

Impact resistance rating (IK)	IK09
IP	66
Ambient temperature - min	-40 °C
Ambient temperature - max	40 °C

1887 - Rodio HE - asymmetric

Code: 414741-39

MATERIALS AND COLOURS



DOWNLOAD

MOUNTS

AssemblyInstructions rodio 05-24.pdf

DESIGNS

TechnicalDrawing 1887he.dxf



Housing	in die-cast aluminium with cooling fins integrated in the cover.
Optics	in high-performance PMMA resistant to high temperatures and UV rays.
Diffuser	tempered glass, 5 mm thick, resistant to thermal shock and impact (UNI EN 12150-1:2001).
Heat sink	the heat sink is designed and made to allow the LEDs to operate at temperatures capable of ensuring excellent performance/output and long service life.
Coating	the fully automated powder-coating cycle involves a polyester-based, salt-spray corrosion-resistant and UV-stabilised paint.
Special coating (UPON REQUEST)	<ul style="list-style-type: none">- Upon request: protective coating recommended for marine environments within 5 km (3 miles) of the sea.- Upon request: conformal coating compliant, subcode -38 with high chemical resistance for environments with a high concentration of chlorine
Colour	Graphite
Equipment	<ul style="list-style-type: none">- with galvanised and painted bracket- waterproof connector for quick installation with no need to open the fixture- EN 61547 compliant surge protection- anti-condensation valve- silicone rubber gasket- external screws and bolts in stainless steel

STANDARDS AND COMPLIANCE

Photobiological safety class	RG0 Ethr
Markings and tests	CE, ENEC
Reference standards	EN60598-1. They have a degree of protection according to the EN60529 standard.
Energy Label	C

GEAR

Upon request	<ul style="list-style-type: none">- protection of up to 10kV. Virtual midnight (subcode -30)- amber LED (subcode -73 - 2200K)- possibility of central light management or with external presence/light sensors.special version (with conformal coating treatment with subcode -38) featuring high chemical resistance for environments with high chlorine content.
--------------	---

WARRANTY

After sales warranty	5 yr
----------------------	------

1887 - Rodio HE - asymmetric


Code: 414741-39



334 Connection for diam. 76 pole



333 Connection for diam. 60 pole



350 Protection grid - Rodio 36LED