

1893 - Rodio - street optics - large areas

Code: 414779-39

GENERAL INFORMATION



Article	1893 - Rodio - street optics - large areas
Code	414779-39

DIMENSIONS AND WEIGHT

Length (mm)	568 mm
Width (mm)	333 mm
Height (mm)	80 mm
Weight (Kg)	6.5 kg

INSTALLATION

Surface exposed to wind (mm)	L 39000 mm ² , F 142000 mm ²
------------------------------	--

ELECTRICAL CHARACTERISTICS AND CONTROLS

Voltage type	AC
Min Voltage (V)	220 V
Max Voltage (V)	240 V
Min Frequency (Hz)	50 Hz
Max Frequency (Hz)	60 Hz
Frequency (Hz)	50 Hz
Wiring name	CLD
Power factor	≥0.9
Surge protector (common) (EN 61547)	10 kV, 10 kV
Insulation class	Class I
Controllability	None



Many different designs, with different wattages and optics for a result that is always of the highest quality. These luminaires are ideal for illuminating façades, street, sports facilities, residential areas and in any outdoor application.


The Rodio family comprises several versions, with asymmetric, narrow-beam and wide-beam optics, also available in wide beam and street curve versions, and Virtual Midnight option. Equipped with LEDs, these luminaires offer perfect glare-free light control. You can choose versions with lenses or with COB LEDs for better lighting performance. All models feature high light quality, colour temperatures of 3000 or 4000K and excellent colour rendering. Also available in Amber colour versions.



1893 - Rodio - street optics - large areas

Code: 414779-39

PHOTOMETRIC DATA



Lighting source	LED
CRI	80
Luminous flux (output) (lm)	19987 lm
Power absorption (total) (W)	157 W
CCT	3000 K
Luminous efficacy (lm/W)	127 lm/W
Low Flicker	luminaire with very low flicker: evenly distributed light for greater visual safety.
Colour consistency	SDCM4
LED flux maintenance	80000 hr, L 80, B 20

MECHANICAL CHARACTERISTICS


Impact resistance rating (IK)	IK08
IP	66
Ambient temperature - min	-40 °C
Ambient temperature - max	40 °C



1893 - Rodio - street optics - large areas

Code: 414779-39

MATERIALS AND COLOURS



DOWNLOAD

MOUNTS

[AssemblyInstructions rodio 05-24.pdf](#)

DESIGNS

[TechnicalDrawing 1893.dxf](#)



Housing	in die-cast aluminium with cooling fins integrated in the cover.
Optics	in high-performance PMMA resistant to high temperatures and UV rays.
Diffuser	tempered glass, 5 mm thick, resistant to thermal shock and impact (UNI EN 12150-1:2001).
Heat sink	the heat sink is designed and made to allow the LEDs to operate at temperatures capable of ensuring excellent performance/output and long service life.
Coating	pre-treatment of metal surface, polyester powder coating to ensure resistance to corrosion and salt spray fogs, UV stabilised.
Special coating (UPON REQUEST)	<ul style="list-style-type: none"> - Upon request: protective coating recommended for marine environments within 5 km (3 miles) of the sea. - Upon request: conformal coating compliant, subcode -38 with high chemical resistance for environments with a high concentration of chlorine
Colour	Graphite
Equipment	<ul style="list-style-type: none"> - with galvanised and painted bracket - waterproof connector for quick installation with no need to open the fixture - EN 61547 compliant surge protection - anti-condensation valve - silicone rubber gasket - external screws and bolts in stainless steel

STANDARDS AND COMPLIANCE

Photobiological safety class	RG0 Ethr
Markings and tests	CE, ENEC
Reference standards	EN60598-1. They have a degree of protection according to the EN60529 standard.
Energy Label	C

GEAR


Upon request	<ul style="list-style-type: none"> - protection of up to 10kV. - Virtual midnight (subcode -30) - amber LED (subcode -73 - 2200K) - possibility of central light management or with external presence/light sensors. - special version (with conformal coating treatment with subcode -38) featuring high chemical resistance for environments with high chlorine content.
--------------	---

WARRANTY

After sales warranty	5 yr
----------------------	------

1893 - Rodio - street optics - large areas


Code: 414779-39




350 Protection grid - Rodio 36LED



333 Connection for diam. 60 pole



334 Connection for diam. 76 pole



350 Protection grid - Rodio 12-24LED