

1984 - Micro Rodio - symmetric wide beam

Code: 414892-39

GENERAL INFORMATION



To meet the needs of those lighting projects where the size of the fixture makes the difference, Disano has created Micro Rodio, the floodlight that concentrates all the technology of the Rodio family into extremely compact dimensions. Also available with COB LED for a greater lighting quality, it stands out for a very long lamp life thanks to top quality materials and LED sources.



Article	1984 - Micro Rodio - symmetric wide beam
Code	414892-39

DIMENSIONS AND WEIGHT

Length (mm)	145 mm
Width (mm)	45 mm
Height (mm)	227 mm
Weight (Kg)	1.15 kg

INSTALLATION

Surface exposed to wind (mm)	L 8600 mm², F 27800 mm²
------------------------------	-------------------------


ELECTRICAL CHARACTERISTICS AND CONTROLS

Voltage type	AC
Min Voltage (V)	220 V
Max Voltage (V)	240 V
Min Frequency (Hz)	50 Hz
Max Frequency (Hz)	60 Hz
Frequency (Hz)	50 Hz
Wiring name	CLD
Power factor	≥0.9
Surge protector (common) (EN 61547)	1 kV, 2 kV
Insulation class	Class I
Controllability	None

1984 - Micro Rodio - symmetric wide beam

Code: 414892-39

PHOTOMETRIC DATA



Lighting source	LED
CRI	80
Luminous flux (output) (lm)	2842 lm
Power absorption (total) (W)	28 W
CCT	3000 K
Luminous efficacy (lm/W)	102 lm/W
Low Flicker	luminaire with very low flicker: evenly distributed light for greater visual safety.
LED flux maintenance	50000 hr, L 80, B 20


MECHANICAL CHARACTERISTICS

Impact resistance rating (IK)	IK08
IP	66
Ambient temperature - min	-20 °C
Ambient temperature - max	40 °C

1984 - Micro Rodio - symmetric wide beam

Code: 414892-39

MATERIALS AND COLOURS



DOWNLOAD

MOUNTS

AssemblyInstructions microrodio 09-22.pdf

DESIGNS

BIM 1984 Micro Rodio.zip

TechnicalDrawing 1984.dxf

TechnicalDrawing3D disano 1984 microrodio.3ds



Housing	in die-cast aluminium with cooling fins integrated in the cover.
Optics	in high-performance PMMA resistant to high temperatures and UV rays.
Diffuser	tempered glass, 4 mm thick, resistant to thermal shock and impact (UNI EN 12150-1:2001).
Heat sink	the heat sink is designed and made to allow the LEDs to operate at temperatures capable of ensuring excellent performance/output and long service life.
Coating	pre-treatment of metal surface, polyester powder coating to ensure resistance to corrosion and salt spray fogs, UV stabilised.
Special coating (UPON REQUEST)	upon request: available with coating tested to withstand corrosion tests in aggressive artificial atmospheres (UNI EN ISO 9227) or marine environments (sea front).
Colour	Anthracite
Equipment	<ul style="list-style-type: none"> - with galvanised and painted bracket - cable for electrical connection - EN 61547 compliant surge protection - silicone rubber gasket - external screws and bolts in stainless steel.

STANDARDS AND COMPLIANCE

Photobiological safety class	RG0 Ethr
Markings and tests	CE
Reference standards	EN60598-1. With degree of protection according to EN60529. Registered Design DM/100271.
Energy Label	C

GEAR

Upon request	<ul style="list-style-type: none"> - version with presence sensor (subcode -19) - double insulation (subcode -14) - CLD-D-D (DALI) wiring (subcode -0041)
--------------	--

WARRANTY

After sales warranty	5 yr
----------------------	------

1984 - Micro Rodio - symmetric wide beam

Code: 414892-39

