Code: 420410-73

CLD		\mathbf{A}					P
IP65	IK08		Colour quality	Ag /	RG0 Ethr	CE	



Characterised by a careful attention to detail and a beautiful finish, Cilindro is a lighting fixture that also emits high quality light. Indirect/direct lighting or only direct lighting used in a modular manner can enhanche full and empty spaces, highlight external architectural details, and give dynamism to surfaces in refined interiors interiors.


The Cilindro lamp can be surface-mounted or used as a pendant.



		GENERAL INFORMATION
Article	1293 - Cilindro 4	
Code	420410-73	
		DIMENSIONS AND WEIGHT
Length (mm)	280 mm	
Width (mm)	185 mm	
Height (mm)	350 mm	
Weight (Kg)	5.5 kg	
		ELECTRICAL CHARACTERISTICS AND CONTROLS
Voltage type	AC	
Min Voltage (V)	220 V	
Max Voltage (V)	240 V	
Min Frequency (Hz)	50 Hz	
Max Frequency (Hz)	60 Hz	
Frequency (Hz)	50 Hz	
Wiring name	CLD	
Power factor	≥0.9	
Insulation class	Class I	
Controllability	None	



Code: 420410-73



Lighting source	LED COB AMBER
CRI	amber
Luminous flux (output) (lm)	3470 lm
Power absorption (total) (W)	40 W
ССТ	2200 K
Luminous efficacy (Im/W)	87 lm/W
LED flux maintenance	50000 hr, L 70, B 50
LED flux maintenance	50000 hr, L 70, B 50 MECHANICAL CHARACTERISTICS
LED flux maintenance	

PHOTOMETRIC DATA





Code: 42041	.0-73		MATERIALS AND COLOURS
	280	Housing	in die-cast aluminium.
350		Diffuser	tempered glass, 4 mm thick, resistant to thermal shock and impact (UNI EN 12150-1:2001).
		Coating	the fully automated powder-coating cycle involves a polyester-based, salt- spray corrosion-resistant and UV-stabilised paint.
		Colour	Grey
		Equipment	built-in temperature controller with auto-reset. Surge protection in compliance with EN61547.
			STANDARDS AND COMPLIANCE
		Photobiological safety class	RG0 Ethr
185		Markings and tests	CE
·		Reference standards	EN60598-1. They have a degree of protection according to the EN60529 standard.
	DOWNLOAD	Energy Label	E
MOUNTS	DOWNLOAD		WARRANTY
WICONTS	A second bulk structure (200) 40, 20 s. If	After sales warranty	3 yr
	AssemblyInstructions 1293 10-22.pdf		
DESIGNS			

TechnicalDrawing 1293g.dxf





Code: 420410-73 asge Wall-mount Pegaso slab asge Wall-mount Pegaso slab

