


1844 - Globo 2.0 - ø360 - CCT-POWER SWITCH

Code: 427250-07

GENERAL INFORMATION




Article	1844 - Globo 2.0 - ø360 - CCT-POWER SWITCH
Code	427250-07

DIMENSIONS AND WEIGHT

Height (mm)	72 mm
Diameter (Ø) (mm)	360 mm
Weight (Kg)	1.4 kg

ELECTRICAL CHARACTERISTICS AND CONTROLS

Voltage type	AC
Min Voltage (V)	220 V
Max Voltage (V)	240 V
Min Frequency (Hz)	50 Hz
Max Frequency (Hz)	60 Hz
Frequency (Hz)	50 Hz
Wiring name	CLD-E
Power factor	≥0.9
Insulation class	Class II
Controllability	None




Globo is a versatile and robust family of wall-mounted or surface-mounted luminaires, designed for both indoor and outdoor lighting. Constructed with a durable, self-extinguishing polycarbonate body, these luminaires feature IP65 protection and double insulation for reliability and safety in any environment. In the CCT and POWER switch versions, the range includes luminaires in various sizes and wattages, allowing for tailored solutions to suit any installation site. The innovative CCT switch technology revolutionises lighting design by enabling easy adjustment of power and colour temperature. This flexibility ensures that the perfect light can be achieved for every project with minimal effort. With a single product code, installers gain access to a wide range of options, simplifying inventory management and streamlining installation. By selecting the appropriate power and LED colour for the specific needs of a space, Globo guarantees optimal lighting performance and design versatility for any application.



1844 - Globo 2.0 - ø360 - CCT-POWER SWITCH

Code: 427250-07

PHOTOMETRIC DATA



Lighting source	LED
CRI	>80
Luminous flux (output) (lm)	1625 lm
Power absorption (total) (W)	13 W
CCT	4000 K
Luminous efficacy (lm/W)	125 lm/W
LED flux maintenance	60000 hr, L 80, B 20

MECHANICAL CHARACTERISTICS

Impact resistance rating (IK)	IK08
IP	65



1844 - Globo 2.0 - ø360 - CCT-POWER SWITCH

Code: 427250-07

MATERIALS AND COLOURS

Housing	UV-stabilised anti-yellowing polypropylene.
Colour	White

EMERGENCY LIGHTING


Type of emergency	S.A.
Emergency operation time	1h

STANDARDS AND COMPLIANCE

Photobiological safety class	RG0
Markings and tests	CE
Reference standards	EN60598-1. They have a degree of protection according to the EN60529 standard.

WARRANTY

After sales warranty	3 yr
----------------------	------



DOWNLOAD

MOUNTS

AssemblyInstructions 1844 12-24.pdf

DESIGNS

TechnicalDrawing globo360.dxf




1844 - Globo 2.0 - ø360 - CCT-POWER SWITCH

Code	TotW	K - Lumen Output - CRI
427250-XX	13	3000K - 1945lm - CRI>80
427250-XX	13	4000K - 1625lm - CRI>80
427250-XX	13	5700K - 1560lm - CRI>80
427250-XX	18	3000K - 1980lm - CRI>80
427250-XX	18	4000K - 2160lm - CRI>80
427250-XX	18	5700K - 2070lm - CRI>80

1844 - Globo 2.0 - ø360 - CCT-POWER SWITCH

Code: 427250-07



2516 Electrified suspension