## 1845 - Cubo LED

# Code: 427445-00





1845 Cubo LED



GENERAL INFORMATION			
	1845 - Cubo LED	Article	
	427445-00	Code	
DIMENSIONS AND WEIGHT			
	322 mm	Length (mm)	

322 mm
322 mm
190 mm
1.6 kg

#### **ELECTRICAL CHARACTERISTICS AND CONTROLS**

Voltage type	AC
Min Voltage (V)	220 V
Max Voltage (V)	240 V
Min Frequency (Hz)	50 Hz
Max Frequency (Hz)	60 Hz
Frequency (Hz)	50 Hz
Wiring name	CLD
Power factor	≥0.85
Insulation class	Class I
Controllability	None



## 1845 - Cubo LED

Code: 427445-00
7150
1053
96
85
75 75
140
55
45


		PHOTOMETRIC DATA
Lighting source	LED	
CRI	≥80	
Luminous flux (output) (lm)	931 lm	
Power absorption (total) (W)	7 W	
ССТ	4000 K	
Luminous efficacy (lm/W)	133 lm/W	
LED flux maintenance	50000 hr, L 80, B 20	
		MECHANICAL CHARACTERISTICS
Impact resistance rating (IK)	IK08	


65





Code: 427445-00





Housing	in polycarbonate, shatterproof and V2 self-extinguishing, UV stablised, anti-yellowing.
Diffuser	in anti-glare matt polycarbonate, shatterproof and V2 self-extinguishing, UV stablised, anti-yellowing, externally smooth and dustproof.
Colour	Grey
Equipment	gasket in eco-friendly material. Rubber cable gland with diam. 1/2 gas inch (cable min. diam.9 max diam. 12).

### STANDARDS AND COMPLIANCE

MATERIALS AND COLOURS

Photobiological safety class	RG0
Markings and tests	CE
Reference standards	EN60598-1. With degree of protection according to EN60529.
Energy Label	С

### WARRANTY

After sales warranty	3 yr

### DOWNLOAD

MOUNTS

AssemblyInstructions cubo-orma 09-22.pdf

**DESIGNS** 

TechnicalDrawing 1845.dxf



