Code: 431829-00

				IP65	IK08
LOW ELICKER	Colpur quality	RG0 Ethr	SURGE		CE




Restyling of the classic garden spotlight with a slender shape. The LED in outdoor lighting is now a guarantee for quality with the advantage of significant energy savings. In the LED version, Koala ensures excellent colour rendering that guarantee perfect, homogeneous light, especially for the lighting of monuments or building façades. Carefully designed for maximum efficiency and durability. Available with multiple accessories and in three colours: silver, graphite, corten.



		GENERAL INFORMATION
Article	1537 - Koala - COB	
Code	431829-00	
		DIMENSIONS AND WEIGHT
Height (mm)	196 mm	
Diameter (Ø) (mm)	127 mm	
Weight (Kg)	0.8 kg	
		ELECTRICAL CHARACTERISTICS AND CONTROLS
Voltage type	AC	
Min Voltage (V)	220 V	
Max Voltage (V)	240 V	
Min Frequency (Hz)	50 Hz	
Max Frequency (Hz)	60 Hz	
Frequency (Hz)	50 Hz	
Wiring name	CLD	
Power factor	≥0.9	
Insulation class	Class I	
Controllability	None	



Code: 431829-00



Lighting source	LED COB	
CRI	80	
Luminous flux (output) (lm)	1195 lm	
Power absorption (total) (W)	15 W	
ССТ	3000 K	
Luminous efficacy (lm/W)	80 lm/W	
Beam angle	46 °	
LED flux maintenance	50000 hr, L 70, B 50	
		MECHANICAL CHARACTERISTICS
Impact resistance rating (IK)	IK08	
IP	65	


PHOTOMETRIC DATA





Please contact the Consulting and Design Centre for any technical information. The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The total wattage absorbed by the system will not exceed 10% of the reported value. Technical lighting data may be subject to changes and improvements due to the fast evolution of the technology. Wednesday, December 25, 2024

Code: 431829-00



	MATERIALS AND COLOURS		
Housing	in die-cast aluminium with cooling fins integrated in the cover.		
Optics	in high-performance metallised polycarbonate.		
Diffuser	screen-printed, tempered glass.		
Coating	pre-treatment of metal surface, polyester powder coating, resistance to corrosion, UV stabilised. Standard with coating for marine environments in compliance with UNI EN ISO 9227.		
Special coating (UPON REQUEST)	Upon request: protective coating recommended for marine environments within 5 km (3 miles) of the sea.		
Colour	Graphite		
Equipment	cable gland diam. 3/8.		
	STANDARDS AND COMPLIANCE		
Photobiological safety class	RG0 Ethr		
Markings and tests	CE		
Reference standards	EN60598-1. With degree of protection according to EN60529.		
Energy Label	E		
	WARRANTY		
After sales warranty	3 yr		

MOUNTS

AssemblyInstructions KOALA 09-22.pdf

DESIGNS

BIM 1537 Koala - COB

DOWNLOAD


TechnicalDrawing 1537di.dxf





illuminazione

Please contact the Consulting and Design Centre for any technical information. The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The total wattage absorbed by the system will not exceed 10% of the reported value. Technical lighting data may be subject to changes and improvements due to the fast evolution of the technology. Wednesday, December 25, 2024





Please contact the Consulting and Design Centre for any technical information. The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The total wattage absorbed by the system will not exceed 10% of the reported value. Technical lighting data may be subject to changes and improvements due to the fast evolution of the technology. Wednesday, December 25, 2024