

1673 - Starled - rectangular 230V

Code: 530697-00

GENERAL INFORMATION



Article	1673 - Starled - rectangular 230V
Code	530697-00

DIMENSIONS AND WEIGHT

Length (mm)	133 mm
Width (mm)	95 mm
Height (mm)	87 mm
Weight (Kg)	0.4 kg

INSTALLATION

Recessed dimensions - Length (mm)	127 mm
Recessed dimensions - Width (mm)	89 mm

ELECTRICAL CHARACTERISTICS AND CONTROLS

Voltage type	AC
Min Voltage (V)	220 V
Max Voltage (V)	240 V
Frequency (Hz)	0 Hz
Wiring name	CLD
Wiring	power supply 220-240V 50/60Hz.
Power factor	≥0.9
Insulation class	Class II
Controllability	None




Starled is a family of in-ground recessed LED fixtures designed to offer maximum versatility. Available in round and square versions, with different types of lenses, it allows the light output to be tailored to any design requirement. Ideal for enhancing pathways, façades, and outdoor spaces, it ensures durability, reliability, and precise, controlled lighting. A complete solution that combines flexibility, quality, and design.



1673 - Starled - rectangular 230V

Code: 530697-00

PHOTOMETRIC DATA



Lighting source	LED
CRI	>80
Luminous flux (output) (lm)	43 lm
Power absorption (total) (W)	1 W
CCT	4000 K
Luminous efficacy (lm/W)	43 lm/W
Beam angle	120 °
LED flux maintenance	50000 hr, L 90, B 10

MECHANICAL CHARACTERISTICS


Impact resistance rating (IK)	IK08
IP	67



1673 - Starled - rectangular 230V

Code: 530697-00

MATERIALS AND COLOURS



Housing	in glass sphere nylon, shatterproof, frame in die-cast aluminium.
Diffuser	matt glass, resistant to thermal shock and impact (UNI EN 12150-1:2001).
Coating	the fully automated powder-coating cycle involves a polyester-based, salt-spray corrosion-resistant and UV-stabilised paint.
Colour	Grey
Equipment	silicone and EPDM rubber sealing gasket.

driveway lamp. Keep clear.

STANDARDS AND COMPLIANCE

Photobiological safety class	RG0
Markings and tests	CE
Reference standards	EN60598-1. They have a degree of protection according to the EN60529 standard.
Laboratory Tests	the luminaire passed the static load resistance test (EN 60598-2-13) with an applied weight of 40KN equal to 2000 kg.
Energy Label	F

DOWNLOAD

MOUNTS

[AssemblyInstructions 1673.pdf](#)

DESIGNS

[TechnicalDrawing 1623.dxf](#)



WARRANTY

After sales warranty	3 yr
----------------------	------